METHOD STATEMENT

Work Activity: Damp Mopping using Kentucky Mop

Site: Various

Location of Work: Various

Risk Assessment Ref: 20

Date: 10/05/2023

MANDATORY PPE	Gloves where required.			
	А	lso as required by the relevant COSHH assessments.		
TRAINING / COMPETENCY	In House training via uHub / Demonstration by supervisor / experienced team member			
MATERIALS & EQUIPMENT	brush/safety	on castors/wringer/sweeping equipment/dustpan and signs and barriers/ floor cleaner/green Scotchbrite pad to ntucky mop/green Scotchbrite hand pad. Chemicals as		
SCOPE OF WORKS	Damp Mopp	oing using Kentucky Mop		
SAFE SEQUENCE OF WORK	2. F 3. 4. F 5. F 6. 7. 7. 7 8. 7 9. 7 10. 5 11. 7 12. 7 13. 6	Put on PPE Place warning signs Ventilate the area, if appropriate Half fill bucket with clean water, add correct dilution ratio of floor cleaner to the water. Pick up large litter or sharp objects with brush and dustpan. If necessary, Dust Control Mop or broom sweeping the floor area. Fit Green Scotchbrite pad over head of Kentucky mop handle, then place Kentucky mop on top and secure both to handle utilising the clip fastener located at the top of the handle. Place Kentucky Mop in mop bucket containing water/detergent solution, agitate mop and place in wringer: slightly twist op handle and squeeze in wringer until mop is damp NOT WET . Commence mopping at the furthest point from the entrance. Firstly, run the mop around the edges to skirting boards taking care not to push mop into corners as this will create a build- up of dirt there. Corners are to be cleaned by hand using a damp cloth and/or Scotchbrite hand pad. Should you encounter any stubborn marks, mop with Scotchbrite face down, then, placing pressure on the mop handle, run mop over the area: turn mop over and mop again (mop side down). Following the above, rinse mop in solution, place in wringer, twist and wring out until mop is damp This procedure should be followed as frequently as required, depending on the size of the area being cleaned. Once again, commencing at the furthest point, work the mop in a side-to-side motion in approximately two metre widths, using		

Document type	Record	Issue date	10/05/2023	©Copyright Ecoserv FM Group Limited
Issue number	001	Document Owner	Compliance Director	Page 1 of 2



ESG-H&S-FRM-003

				01
	14. 15. 16. 17.	overlapping strokes. Avoid splash boards when using this method. Whilst performing the above meth and agitate frequently, ensuring the wrung out and it is left damp, not v Change the water/detergent solut necessary during this operation. R best results. Upon completion of the work, rem head of the handle wash and rinse Return warning signs to store and appropriate	od, rinse mop in the solu lat each time the mop if vet. ion as frequently as is emember, clean water gi ove the Kentucky Mop fro thoroughly and allow to	i ves om
WORKING ENVIRONMENT	No issues			
OTHER SPECIFC CONSIDERATIONS	N/A			
MEMBER OF PUBLIC SAFETY	Signage put in place to all entrances/exits to area being cleaned. Work done out of business hours where possible.			
MANUAL HANDLING	N/A			
HAZARDOUS SUBSTANCES	Please refer to the relevant COSHH assessments for substances being used.			
WORKING AT HEIGHT	N/A			
HOT WORK	N/A			
EMERGENCY		DS and COSHH assessment.		
PROCEDURES	Follow site safety rules along with ensuring compliance with site "workplace" H&S and welfare facilities including location of First Aid Box.			
OPERATIVES HEALTH CONSIDERATIONS	N/A			
WASTE MANAGEMENT	N/A			
OTHER INFORMATION	N/A			

ADDITIONAL POLICIES AND PROCEDURES None

Document type	Record	Issue date	10/05/2023	©Copyright Ecoserv FM
				Group Limited
Issue number	001	Document Owner	Compliance Director	Page 2 of 2